TP-Link Omada EAP650-Outdoor 3000 Mbit/s Weiß Power over Ethernet (PoE)

Marke : TP-Link

Produktfamilie: Omada

Artikel-Code: EAP650-OUTDOOR

Produktname : EAP650-Outdoor

TP-Link Omada EAP650-Outdoor. 2,4 GHz, 5 GHz, Maximale Datenübertragungsrate: 3000 Mbit/s. Unterstützte Sicherheitsalgorithmen: WPA, WPA-Enterprise, WPA2, WPA2-Enterprise, WPA3, WPA3-Enterprise. Ethernet LAN Datentransferraten: 10,100,1000 Mbit/s. Power over Ethernet (PoE). Produktfarbe: Weiß

Merkmale	
2,4 GHz *	✔
5 GHz *	✔
6 GHz *	✘
Maximale Datenübertragungsrate *	3000 Mbit/s
Maximale Datenübertragungsrate (2,4 GHz)	574 Mbit/s
Maximale Datenübertragungsrate (5 GHz)	2402 Mbit/s
Ethernet LAN Datentransferraten	10,100,1000 Mbit/s
Netzstandard	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11ax, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n, IEEE 802.1x, IEEE 802.3at
Verkabelungstechnologie	10/100/1000Base-T(X)
Zahl der Benutzer	250 Benutzer
Automatische Kanalwahl	✔
Automatischer Kanalscan	✔
MIMO	✔
MIMO-Typ	Multi User MIMO
AP-Modus-Eigenschaften anpassen	Vernetzung von Netzen
VLAN-Unterstützung	✔
Ratenbeschränkung	✔
Bandsteuerung	✔
Airtime Fairness (ATF)	✔
Quality of Service (QoS) Support	✔
BeamForming	✔

Anschlüsse und Schnittstellen	
Anzahl Ethernet-LAN-Anschlüsse (RJ-45) *	1
Energie	
Power over Ethernet (PoE) *	✔
Design	
Platzierung *	Stange, Wand
Produktfarbe *	Weiß
Internationale Schutzart (IP-Code)	IP67
Reset-Knopf	✔
LED-Anzeigen	✔
Antenne	
Antennentyp *	Intern
Antennenrichtungsart	Mit kugelförmiger Richtcharakteristik
Zertifikate	
Zertifizierung	CE, FCC, RoHS
Gewicht und Abmessungen	
Breite	280,4 mm
Tiefe	106,5 mm
Höhe	56,8 mm
Lieferumfang	
Menge pro Packung	1 Stück(e)
Montageset	✔
Schnellstartübersicht	✔

Sicherheit	
Unterstützte Sicherheitsalgorithmen *	WPA, WPA-Enterprise, WPA2, WPA2-Enterprise, WPA3, WPA3-Enterprise
MAC Adressen Filtern	✔
Funktionen Service Set Identifier (SSID)	Multiple SSIDs, SSID-Übertragung ein/aus

Betriebsbedingungen	
Relative Luftfeuchtigkeit in Betrieb	10 - 90%
Betriebstemperatur	-30 - 70 °C
Temperaturbereich bei Lagerung	-40 - 70 °C
Luftfeuchtigkeit bei Lagerung	5 - 90%

4897098682098

4897098683552

0840030703553

840030703553

Catalog Object Cloud

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 01-JUL-2026. Prints or copies of Information are only valid on the printed Publication date